



## Flash Photography

Diffuse the flash

“Bounce”

Umbrella, soft-box etc.

Create Depth with Shadow – Use “Unequal” Light

Two flashes or flash + reflector

Get the Flash Off the Camera

## Getting the Flash Off Camera – Connections

Wired

Sync (PC) cable – “dumb”

TTL cable – “smart”

Wireless

Slave Photosensor – “dumb”

Radio Triggers\*– “dumb”

CLS – “smart”

\* Pocket Wizard, etc.  
New version of PWs are “smart”

## Connections – “Dumb” vs. “Smart”

### “Dumb”

- All manual (exposure, flash power, etc)
- Changing settings on a flash requires that you have it in hand
- Connection just tells off camera flashes that you triggered the shutter

### “Smart”

- Takes advantage of iTTL
- Connection allows communication between camera and off camera flashes.
- Can change settings on flash remotely

## CLS Technology

Camera gathers and analyzes data (exposure, focus distance, returns from pre-flashes, etc.) and decides on how flash should be set.

On camera flash (in “controller” mode) sends this data to other flashes (in “remote” mode).

Data is sent via pulses of light so remotes must be able to “see” controller.

“line of sight”; bright sun can interfere

All flashes respond “appropriately” when shutter is triggered.

Multiple flashes (or groups) can be controlled independently

## Setting Built-in Flash to Act as CLS Controller



### e3: Flash Cntrl for Built-in Flash

Choose the flash mode for the built-in flash.


D300 version

Option	Description
TTL (default)	Flash output is adjusted automatically in response to shooting conditions.
M Manual	Choose the flash level (pg. 292).
RPT Repeating flash	The flash fires repeatedly while the shutter is open, producing a strobe-light effect (pg. 292).
C Commander mode	Use the built-in flash as a master flash controlling one or more remote optional flash units (pg. 293).

Also need to set the off-camera flash(es) to “remote”

CLS is not available in all cameras –  
available in D70 and “above”  
not available in D40  
available using selected external flashes as controller in D3000


## Commander Mode



Option	Description
<b>Built-in flash</b>	Choose a flash mode for the built-in flash (commander flash).
TTL	i-TTL mode. Choose flash compensation from values between +3.0 and –3.0 EV in increments of 1/3 EV.
M	Choose the flash level from values between [Full] and [1/128] (1/128 of full power).
--	The built-in flash does not fire, but the AF-assist illuminator lights. The built-in flash must be raised so that it can emit monitor pre-flashes.
<b>Group A</b>	Choose a flash mode for all flash units in group A.
TTL	i-TTL mode. Choose flash compensation from values between +3.0 and –3.0 EV in increments of 1/3 EV.
AA	Auto aperture (available only with SB-900 and SB-800 flash units). Choose flash compensation from values between +3.0 and –3.0 EV in increments of 1/3 EV.
M	Choose the flash level from values between [Full] and [1/128] (1/128 of full power).
--	The flash units in this group do not fire.



D300 version

## Focus Mode




Option	Description
<b>S</b> Single-servo AF	Camera focuses when shutter-release button is pressed halfway. Focus locks when in-focus indicator (●) appears in viewfinder, and remains locked while shutter-release button is pressed halfway ( <i>focus lock</i> ). At default settings, shutter can only be released when in-focus indicator is displayed ( <i>focus priority</i> ).
<b>C</b> Continuous- servo AF	Camera focuses continuously while shutter-release button is pressed halfway. If subject moves, camera will engage <i>predictive focus tracking</i> (pg. 63) to predict final distance to subject and adjust focus as necessary. At default settings, shutter can be released whether or not subject is in focus ( <i>release priority</i> ).
<b>M</b> Manual (pg. 71)	Camera does not focus automatically; focus must be adjusted manually using the lens focusing ring. If maximum aperture of lens is f/5.6 or faster, viewfinder focus indicator can be used to confirm focus ( <i>electronic range finding</i> ; pg. 72), but photographs can be taken at any time, whether or not subject is in focus.

## Auto-Focus Area Mode



AF-area mode  
indicator (top panel)

Mode	Description
<b>[ ]</b> Single- point AF	User selects focus point manually; camera focuses on subject in selected focus point only. Use for relatively static compositions with subjects that will stay in selected focus point.
<b>[ ]</b> Dynamic- area AF	<ul style="list-style-type: none"> <li>• In <b>continuous-servo AF</b> (pg 62), user selects focus point manually; if subject briefly leaves selected focus point, camera will focus based on information from surrounding points. Number of focus points used can be selected from 9, 21, and 51 using Custom Setting a3 ([Dynamic AF area], pg. 269). If [51 points (3D-tracking)] is selected for Custom Setting a3, focus point will be selected automatically using 3D-tracking.</li> <li>• In <b>single-servo AF</b>, user selects focus point manually; camera focuses on subject in selected focus point only.</li> </ul>
<b>[ ]</b> Auto-area AF	Camera automatically detects subject and selects focus point. If type G or D lens is used, camera can distinguish human subjects from background for improved subject detection. In single-servo AF, active focus points are highlighted for about one second after camera focuses. Active focus points are not displayed in continuous-servo AF.



## Number of Focus Points

AF-area mode		Control panel
[•] Single-point AF		[ • ]
[••] Dynamic-area AF *	Custom Setting a3 ([Dynamic AF area], pg. 269)	
	9 points (default)	[ 3x3 ]
	21 points	[ 3x7 ]
	51 points	[ 9x6 ]
[•••] Auto-area AF	51 points (3D-tracking)	[ 9x6 ] 3D
		[ 9x6 ] AUTO

\* Only active focus point is displayed in the viewfinder. Remaining focus points provide information to assist focus operation.

## Custom Functions


Explore and experiment.... Repeat often!

What follows are some of my custom settings and, importantly, why I have set them this way

Remember... my settings are not yours!

All refer to D300

Options will be different on other models



## Metering / Exposure

### b: Metering/Exposure

#### b1: ISO Sensitivity Step Value

This option determines whether adjustments to sensitivity are made in increments equivalent to  $\frac{1}{3}$  EV,  $\frac{1}{2}$  EV, or 1 EV.

Option
$\frac{1}{3}$ $\frac{1}{3}$ step (default)
$\frac{1}{2}$ $\frac{1}{2}$ step
1 1 step

#### b2: EV Steps for Exposure Cntrl.

This option determines whether adjustments to shutter speed, aperture, and bracketing are made in increments equivalent to  $\frac{1}{3}$  EV,  $\frac{1}{2}$  EV, or 1 EV.

Option	Description
$\frac{1}{3}$ $\frac{1}{3}$ step (default)	Changes to shutter speed and aperture are in increments equivalent to $\frac{1}{3}$ EV. The bracketing increment can be selected from $\frac{1}{3}$ , $\frac{2}{3}$ , and 1 EV.
$\frac{1}{2}$ $\frac{1}{2}$ step	Changes to shutter speed and aperture are in increments equivalent to $\frac{1}{2}$ EV. The bracketing increment can be selected from $\frac{1}{2}$ and 1 EV.
1 1 step	Changes to shutter speed and aperture are in increments equivalent to 1 EV. The bracketing increment is set to 1 EV.

#### b3: Exp Comp/Fine Tune

This option determines whether adjustments to exposure and flash compensation are made in increments equivalent to  $\frac{1}{3}$  EV,  $\frac{1}{2}$  EV, or 1 EV.

Option
$\frac{1}{3}$ $\frac{1}{3}$ step (default)
$\frac{1}{2}$ $\frac{1}{2}$ step
1 1 step

All set to  $\frac{1}{2}$  stop

Making changes is faster

Don't need the finer granularity

## Delays

### c3: Self-Timer Delay

This option controls the length of the shutter release delay in self-timer mode. Choose from 2 s, 5 s, 10 s, and 20 s.

Option
$\frac{1}{2}$ 2 s
$\frac{1}{5}$ 5 s
$\frac{1}{10}$ 10 s (default)
$\frac{1}{20}$ 20 s

Often use self-timer in place of cable release.

Therefore don't want/need long delay

### c4: Monitor off Delay

This option controls how long the monitor remains on when no operations are performed. Choose from 10 s, 20 s, 1 minute, 5 minutes, or 10 minutes. Choose a shorter monitor-off delay for longer battery life. Regardless of the setting chosen, the monitor remains on if no operations are performed for about ten minutes when the camera is powered by an optional EH-5a or EH-5 AC adapter.

Option
$\frac{1}{10}$ 10 s
$\frac{1}{20}$ 20 s (default)
$\frac{1}{1}$ 1 min.
$\frac{1}{5}$ 5 min.
$\frac{1}{10}$ 10 min.

Use LCD mainly to view histogram / highlights





No need for longer – saves battery


## Beep and Grid

### d1: Beep

Choose [High] or [Low] to sound a beep when the self-timer is used or the camera focuses in single-servo autofocus (note that a beep will not sound if [Release] is selected for Custom Setting a2 ([AF-S priority selection], pg. 268)).

Wildlife!


Option	Description
 <b>High</b> (default)	Choose the pitch of the beep from [High] and [Low]. A  icon is displayed in the control panel and shooting information displays.
 <b>Low</b>	
 <b>Off</b>	Turn the beep speaker off.



### d2: Viewfinder Grid Display

Choose whether on-demand grid lines are displayed in the viewfinder (or, in live view mode, in the monitor) for reference when composing photographs.

Helps me get horizons level  
and  
verticals vertical



Option	Description
 <b>On</b>	On-demand grid lines displayed.
<b>Off</b> (default)	On-demand grid lines not displayed.

## Flash Sync Speed

### e1: Flash Sync Speed

This option controls flash sync speed.


High-speed sync is  
one of the wonders of  
modern technology!

Option	Description
 <b>1/320 s</b> (Auto FP)	Use auto FP high-speed sync with SB-900, SB-800, SB-600, and SB-R200 flash units. If other flash units are used, shutter speed is set to 1/320 s. When the camera shows a shutter speed of 1/320 s in exposure mode P or B, auto FP high-speed sync will be activated if the actual shutter speed is faster than 1/320 s.
 <b>1/250 s</b> (Auto FP)	Use auto FP high-speed sync with SB-900, SB-800, SB-600, and SB-R200 flash units. If other flash units are used, shutter speed is set to 1/250 s. When the camera shows a shutter speed of 1/250 s in exposure mode P or B, auto FP high-speed sync will be activated if the actual shutter speed is faster than 1/250 s.
<b>1/250 s</b> (default)	Flash sync speed set to 1/250 s.
<b>1/200 s</b>	Flash sync speed set to 1/200 s.
<b>1/160 s</b>	Flash sync speed set to 1/160 s.
<b>1/125 s</b>	Flash sync speed set to 1/125 s.
<b>1/100 s</b>	Flash sync speed set to 1/100 s.
<b>1/80 s</b>	Flash sync speed set to 1/80 s.
<b>1/60 s</b>	Flash sync speed set to 1/60 s.



## Copyright Info

- [Done]: Save changes and return to the setup menu.
- [Artist]: Enter a photographer name as described on page 256. Photographer names can be up to 36 characters long.
- [Copyright]: Enter the name of the copyright holder as described on page 256. Copyright holder names can be up to 54 characters long.
- [Attach copyright information]: Select this option to attach copyright information to all subsequent photographs. [Attach copyright information] can be turned on and off by highlighting it and pressing ►.



Found on set-up menu not on custom setting menu

## Recent Settings / My Menu

### Displaying Recent Settings

To display the twenty most recently used settings, select [Recent settings] for [My Menu] > [Choose tab].

#### 1 Select [Choose tab].

In My Menu (MENU), highlight [Choose tab] and press ►.



#### 2 Select [Recent settings].

Highlight [Recent settings] and press OK. The name of the menu will change from "MY MENU" to "RECENT SETTINGS."



Menu items will be added to the top of the recent settings menu as they are used. To view My Menu again, select [My Menu] for [Recent settings] > [Choose tab].

## My Menu

### **My Menu: Creating a Custom Menu**

The [My Menu] option can be used to create and edit a customized list of options from the playback, shooting, Custom Settings, setup, and retouch menus for quick access (up to 20 items). If desired, recent settings can be displayed in place of My Menu (pg. 348).

Options can be added, deleted, and reordered as described below. For information on basic menu operations, see "Tutorial: Camera Menus" (pg. 24).



**The End!**

**Thanks for listening... again!**